The Bandit

Tesla Model 3 Front License Plate Holder - Installation Guide

Thank you for choosing **The Bandit** front license plate holder for your Tesla Model 3. This license plate holder is custom designed to the proximity of OEM mount without physical contact with front bumper using 4 1/4-20 bolts secured to the factory grill without any drilling. Hand crafted in Rancho Cordova, CA and constructed of an outdoor grade, black textured marine board, all parts are CNC machined, beveled, completely assembled and ready to install. Tested and compatible with Autopilot and Homelink. Touchless car wash only.

1) Orient the rear brace inward / horizontally towards the center, then slide into 2nd opening from top of factory grill. Repeat for the other side

Note: The top collar stop (A) stops the rear brace from accidental unscrewing and also aids for uninstallation of **The Bandit**



2) Align the rear brace vertically, insert bolt into rear brace hole (split lock washer, then flat washer), then using the included 5/32 hex key, hand-start the 1/4-20 bolt into the threaded insert. Check for center alignment before securing all 4 bolts without over-torquing.



3) Secure your license plate using a Phillips screwdriver with 4 of the #10 x 3/8" screws.

Removal procedure: loosen and remove the bottom bolt as in step 2). Unscrew the top bolt until the rear brace stops at the collar, then slide the rear brace out of the factory grill.



